

# Lid - Wall

## DATA SHEET

PROJECT: \_\_\_\_\_

TYPE: \_\_\_\_\_

NOTES: \_\_\_\_\_

QUANTITY: \_\_\_\_\_

DATE: \_\_\_\_\_

### GENERAL

**Product Code:**

LIDW-575 / LIDW-775 / LIDW-975

**Luminaire Type:**

Wall Mounted

**Body Construction:**

Highest grade extruded aluminum

**Body Surface Finishes:**

Texture White / Texture Black / Texture Grey /  
Any Other RAL color possible on Request

**IP Rating:**

40



### PHYSICAL

**Dimension  $\Phi$  x VH x TH:**

575x45x90mm 775x45x90mm 975x45x90mm

**Fixing System:**

Wall Mounted with Screw

### LED

**Light Source:**

LED

**CCT:**

3000K / 4000K / 5700K

**CRI:**

80+, 90+ (Available on request)

**MacAdam Step:**

3

### OPTICAL

**Light Distribution:**

Direct

**Diffuser:**

Satin finished PC Opal Diffuser (SOD) from  
Germany

### ELECTRICAL

**System Wattage:**

45W / 60W / 75W

**Luminous Flux:**

3150 lm / 4200 lm / 5250 lm

**Power Factor:**

0.94

### DRIVER

Non-Dimmable

DALI Dimmable

0-10V Analogue

Bluetooth 4.0 CASAMBI remote control through App