

# ring0 Slim-Direct-Indirect

## DATA SHEET

PROJECT: \_\_\_\_\_

TYPE: \_\_\_\_\_

NOTES: \_\_\_\_\_

QUANTITY: \_\_\_\_\_

DATE: \_\_\_\_\_

### GENERAL

**Product Code:**

RSP-DI-450 / RSP-DI-600 / RSP-DI-800 / RSP-DI-1000 / RSP-DI-1200 / RSP-DI-1500 / RSP-DI-1800

**Luminaire Type:**

Pendant

**Body Construction:**

Highest grade extruded aluminum

**Body Surface Finishes:**

Texture White / Texture Black / Texture Grey / Any other RAL color available on request

**IP Rating:**

40



### PHYSICAL

**Dimension  $\Phi$  x H x W:**

450x40x20mm 600x40x20mm 800x40x20mm  
1000x40x20mm 1200x40x20mm 1500x40x20mm  
1800x40x20mm

**Fixing System:**

1500mm long steel wires with height adjustment system

### LED

**Light Source:**

LED

**CCT:**

3000K / 4000K / 5700K / TW (Tunable White)  
]-2700-6500K

**CRI:**

80+, 90+ (Available on request)

**MacAdam Step:**

3

### OPTICAL

**Light Distribution:**

Direct-Indirect

### ELECTRICAL

**System Wattage:**

40W / 50W / 60W / 70W / 90W / 110W / 130W

**Luminous Flux:**

2800lm / 3500lm / 4200lm / 4900lm / 6300lm /  
7700lm / 9100lm

**Power Factor:**

0.94

### DRIVER

Non-Dimmable

DALI Dimmable

0-10V Analogue Dimmable

Bluetooth 4.0 CASAMBI remote control through App