

ring0 Slim-Vertical-Direct

DATA SHEET

PROJECT: _____

TYPE: _____

NOTES: _____

QUANTITY: _____

DATE: _____

GENERAL

Product Code:

RSPV-D-450 / RSPV-D-600 / RSPV-D-800 /
RSPV-D-1000 / RSP-D-1200

Luminaire Type:

Pendant in Vertical

Body Construction:

Highest grade extruded aluminum

Body Surface Finishes:

Texture White / Texture Black / Any other RAL
color available on request

IP Rating:

40

PHYSICAL

Dimension Φ x H x W:

450x25x20mm 600x25x20mm 800x25x20mm
1000x25x20mm 1200x25x20mm

Fixing System:

1500mm long steel wires with height
adjustment system

LED

Light Source:

LED

CCT:

3000K / 4000K / 5700K / TW (Tunable White)
-2700-6500K

CRI:

80+, 90+ (Available on request)

MacAdam Step:

3

OPTICAL

Light Distribution:

Direct

Diffuser:

Satin finished Opal Diffuser

ELECTRICAL

System Wattage:

25W / 35W / 40W / 60W / 70W

Luminous Flux:

1750lm / 2450lm / 2800lm / 4200lm / 4900lm

Power Factor:

0.94

DRIVER

Non-Dimmable

DALI Dimmable

0-10V Analogue Dimmable

Bluetooth 4.0 CASAMBI remote control through App

