

# Linear 46 Recessed with Trim

## DATA SHEET

**PROJECT:** \_\_\_\_\_

**TYPE:** \_\_\_\_\_

**NOTES:** \_\_\_\_\_

**QUANTITY:** \_\_\_\_\_

**DATE:** \_\_\_\_\_

### GENERAL

**Product Code:**

RMWT-46-D

**Luminaire Type:**

Recessed

**Body Construction:**

Highest grade extruded aluminum Aluminum profile single max. length available in 3380mm

**Body Surface Finishes:**

Natural anodized finish / Texture White / Texture Black / Texture Grey / Any Other RAL color possible on Request (Any Contrast color also possible)

**IP Rating:**

40



### PHYSICAL

**Dimension W x H x L\*:**

46x75x1130mm

**Fixing System:**

Recessed Mounting Brackets

### LED

**Light Source:**

LED

**CCT:**

3000K / 4000K / 5700K / TW (Tunable White)  
2700-6500K

**CRI:**

80+, 90+, (Available on request)

**MacAdam Step:**

3

### OPTICAL

**Light Distribution:**

Direct

**Diffuser:**

Satin Finished PC Opal Diffuser, Micro-Prismatic Diffuser

**UGR:**

< 22 with Opal Diffuser, < 19 with Micro-Prismatic Diffuser

### ELECTRICAL

**System Wattage:**

23W / 27W

**Luminous Flux:**

2047 lm at Luminaire level / 2295 lm at Luminaire level

**Power Factor:**

0.94

### DRIVER

Non-Dimmable

DALI Dimmable

0-10V Analogue Dimmable

Bluetooth 4.0 CASAMBI remote control through App

\*The length mentioned here is only for a single unit but can be changed as per your preference.

\*customized product, please contact us for required form and patterns.