

Linear 70 - Ceiling-Direct

DATA SHEET

GENERAL

Product Code:

CM-70-D

Luminaire Type:

Ceiling Mounted

Body Construction:

Highest grade extruded aluminum Aluminum profile single max. length available in 3380mm

Body Surface Finishes:

Natural anodized finish / Texture White / Texture Black / Texture Grey / Any Other RAL color possible on Request (Any Contrast color also possible)

IP Rating:

40

PHYSICAL

Dimension W x H x L*:

70x80x1130mm

Fixing System:

Ceiling Mounted with Screw

LED

Light Source:

LED

CCT:

3000K / 4000K / 5700K / TW (Tunable White)
2700-6500K

CRI:

80+, 90+, (Available on request)

MacAdam Step:

3

OPTICAL

Light Distribution:

Direct

Diffuser:

Satin Finished PC Opal Diffuser, Micro-Prismatic Diffuser

UGR:

< 22 with Opal Diffuser, < 19 with Micro-Prismatic Diffuser

ELECTRICAL

System Wattage:

23W / 27W

Luminous Flux:

2047 lm at Luminaire level / 2295 lm at Luminaire level

Power Factor:

0.94

DRIVER

Non-Dimmable

DALI Dimmable

0-10V Analogue Dimmable

Bluetooth 4.0 CASAMBI remote control through App


PROJECT:

TYPE:

NOTES:

QUANTITY:

DATE:



*The length mentioned here is only for a single unit but can be changed as per your preference.

*customized product, please contact us for required form and patterns.