VIZION™
An Architectural Lighting Company

PROJECT:

TYPE:

NOTES:

QUANTITY:

DATE:

Hexedge Hollow (H) - Pendant - Direct-Indirect

DATA SHEET

GENERAL

Product Code:
HPH40-D/I-600 / HPH40-D/I-900

Luminaire Type:
Pendant

Body Construction:
Highest grade extruded aluminum

Body Surface Finishes:
Texture White / Texture Black / Texture Grey / Any Other RAL color possible on Request

IP Rating:
40

PHYSICAL

Dimension Φ x H x W:
600x90x40mm 900x90x40mm

Fixing System:
1500 mm long steel wires with height adjustment system

LED

Light Source:
LED

CCT:
3000K / 4000K / 5700K / TW (Tunable White) 2700-6500K

CRI:
80+, 90+ (Available on request)

MacAdam Step:
3

OPTICAL

Light Distribution:
Direct-Indirect

Diffuser:
Satin Finished PC Opal Diffuser, Micro-Prismatic Diffuser

UGR:
< 22 with Opal Diffuser, < 19 with Micro-Prismatic Diffuser

ELECTRICAL

System Wattage:
75W / 115W

Luminous Flux:
5250 lm / 8050 lm

Power Factor:
0.94

DRIVER

Non-Dimmable

DALI Dimmable

0-10V Analogue

Bluetooth 4.0 CASAMBI remote control through App