

Soft triang0 - Recessed

DATA SHEET

GENERAL

Product Code:

STR-450 / STR-600 / STR-900

Luminaire Type:

Recessed

Body Construction:

Highest grade extruded aluminum

Body Surface Finishes:

Texture White / Texture Black / Texture Grey /  
Any Other RAL color possible on Request

IP Rating:

40

PHYSICAL

Dimension L x H:

450x85mm 600x85mm 900x85mm

Fixing System:

Mounting Bracket for Recessed

LED

Light Source:

LED

CCT:

3000K / 4000K / 5700K / TW (Tunable White)  
2700-6500K Possible only for 600 mm / 900mm

CRI:

80+, 90+ (Available on request)

MacAdam Step:

3

OPTICAL

Light Distribution:

Direct

Diffuser:

Satin Finished PC Opal Diffuser, Micro-  
Prismatic Diffuser

UGR:

< 22 with Opal Diffuser, < 19 with Micro-  
Prismatic Diffuser

ELECTRICAL

System Wattage:

35W / 45W / 75W

Luminous Flux:

2450 lm / 3150lm / 5250lm

Power Factor:

0.94

DRIVER

Non-Dimmable

DALI Dimmable

0-10V Analogue

Bluetooth 4.0 CASAMBI remote control through App

PROJECT:

TYPE:

NOTES:

QUANTITY:

DATE:

