

Hexedge Hollow (H) - Pendant - Direct-Indirect

DATA SHEET

PROJECT:

TYPE:

NOTES:

QUANTITY:

DATE:

GENERAL

Product Code:

HPH40-D/I-600 / HPH40-D/I-900

Luminaire Type:

Pendant

Body Construction:

Highest grade extruded aluminum

Body Surface Finishes:

Texture White / Texture Black / Texture Grey /  
Any Other RAL color possible on Request

IP Rating:

40



PHYSICAL

Dimension  $\Phi$  x H x W:

600x90x40mm 900x90x40mm

Fixing System:

1500 mm long steel wires with height  
adjustment system

LED

Light Source:

LED

CCT:

3000K / 4000K / 5700K / TW (Tunable White)  
2700-6500K

CRI:

80+, 90+ (Available on request)

MacAdam Step:

3

OPTICAL

Light Distribution:

Direct-Indirect

Diffuser:

Satin Finished PC Opal Diffuser, Micro-  
Prismatic Diffuser

UGR:

< 22 with Opal Diffuser, < 19 with Micro-  
Prismatic Diffuser

ELECTRICAL

System Wattage:

75W / 115W

Luminous Flux:

5250 lm / 8050 lm

Power Factor:

0.94

DRIVER

Non-Dimmable  
DALI Dimmable  
0-10V Analogue  
Bluetooth 4.0 CASAMBI remote control through App