

Linear 70 Pendant Direct-Indirect

DATA SHEET

GENERAL

**Product Code:**  
PM-70-DI

**Luminaire Type:**  
Pendant

**Body Construction:**  
Highest grade extruded aluminum Aluminum profile single max. length available in 3380mm

**Body Surface Finishes:**  
Natural anodized finish / Texture White / Texture Black / Texture Grey / Any Other RAL color possible on Request (Any Contrast color also possible)

**IP Rating:**  
40

PHYSICAL

**Dimension W x H x L\*:**  
70x100x1130mm

**Fixing System:**  
1500mm long steel wires with height adjustment system

LED

**Light Source:**  
LED

**CCT:**  
3000K / 4000K / 5700K / TW (Tunable White) 2700-6500K

**CRI:**  
80+, 90+, (Available on request)

**MacAdam Step:**  
3

OPTICAL

**Light Distribution:**  
Direct-Indirect

**Diffuser:**  
Satin Finished PC Opal Diffuser, Micro-Prismatic Diffuser

**UGR:**  
< 22 with Opal Diffuser, < 19 with Micro-Prismatic Diffuser

ELECTRICAL

**System Wattage:**  
23W-D / 11W-U / 27W-D / 13W-U

**Luminous Flux:**  
3026 lm at Luminaire level / 3400 lm at Luminaire level

**Power Factor:**  
0.94

DRIVER

Non-Dimmable

DALI Dimmable

0-10V Analogue Dimmable

Bluetooth 4.0 CASAMBI remote control through App


PROJECT:

TYPE:

NOTES:

QUANTITY:

DATE:



\*The length mentioned here is only for a single unit but can be changed as per your preference.

\*customized product, please contact us for required form and patterns.